

RTD WITH N/U/N & STRAIGHT THERMOWELL

B

R-730

RTD Element		1	Pt-100x1, Simplex	
		2	Pt-100x2, Duplex	
		Other	Consult Factory	
Termination Style		A	Die cast Alu A TYPE	
		B	Die cast Alu B TYPE	
		C1	Die cast Alu IP-67 (Single Entry)	
		C2	Die cast Alu IP-67 (Double Entry)	
		SS	SS- Head	
		M	Miniature Die cast Alu.	
		P	Plastic	
Junction Style		EB1	Die cast Alu Explosion / Flame proof IIB (Zone1& 2)	
		EB2	SS Explosion / Flame proof IIB (Zone1 & 2)	
		EC1	Die cast Alu Explosion / Flame proof IIC (T6)	
		EC2	SS Flame proof IIC (T6)	
		EC3	Die cast Alu Explosion / Flame proof IIC (T6) ATEX	
Sheath "OD"		W2	2- Wire	
		W3	3- Wire	
		W4	4- Wire	
Sheath Material		3	Ø3mm	
		4.5	Ø4.5mm	
		6	Ø6mm	
		8	Ø8mm	
		Other	Consult Factory	
Thermowell Material		316	SS 316	
		Other	Consult Factory	
Thermowell OD (mm)		316	SS 316	
		310	SS 310	
		304	SS 304	
		600	Inconel-600	
		800	Inconel-800	
		446	HRS-446	
		Other	Consult Factory	
ID (mm)		A	1/2" SCH 80	
		B	1/2" SCH 40	
		Other	Consult Factory	
N/U/N		Flange Rating	Flange Size	Flange Material
Length of "T" (mm)		150#	1/2"	SS 316
		300#	3/4"	SS 310
		400#	1"	SS 304
		600#	1 1/2"	Cast Steel
			1 1/4"	
		Other	2"	
Process Connection		Other	Consult Factory	
Flange Material		Threads	1/4"	
			1/2"	
			3/4"	
			3/8"	
		B.S.P. / N.P.T.	1"	
			1 1/4"	
			1 1/2"	
			2"	
		M-Thread	M20X1.5, M18X1.5, M33X2, M27X2	
		Other	Consult Factory	
Inst. Connection		Calibration Standard	A ANSI MC96.1	
Insertion Length (I.L.) (mm)			D DIN	
Extention Length (E.L.) (mm)			I IEC	
Nominal Length of T/C "L" (mm)				